

### SPECIFICATION SHEET

## PRECEDENT® C-600



#### STANDARD FEATURES

- SMART REEFER™ SR-4 Controller
- Diesel Direct Electric (DDE) architecture with ETV
- · Microchannel condenser coils
- · 2-Speed Evaporator
- OptiSet<sup>™</sup> Plus
- CargoWatch™
- · Easy-access door design
- 50-gallon aluminum undermount fuel tank w/visual fuel level gauge
- ServiceWatch™

#### **OPTIONS**

- SmartPower electric standby
  - Standard
  - High output (HO)
- SmartPower prep package
- · Remote monitoring lights
- Arctic package
- · Frost plug heater
- · Battery charger
- Appearance options
- LED lighting kit
- Chrome package
- Fresh air exchange
- Fuel tanks and sensorsPrimAir air management products
- TracKing® telematics
- · CargoLink wireless sensors

#### **EPA COMPLIANCE**

EPA Emissions Compliance: Sub 25HP Tier IV Final

#### CARB COMPLIANCE

California Air Resources Board (CARB): Useful Life - 7 years (see your Thermo King dealer for details)

#### REFRIGERATION CAPACITY

(System net cooling capacity at 100°F ambient and high speed engine operation)

	Engine Power w/ETV	Electric Power*	
	BTU/hr Watts	BTU/hr Watts	
35°F	59,000 16,998	51,000 14, 947	
0°F	34,000 9,964	34,000 9,964	
-20°F	21,000 6,154	21,000 6,154	

<sup>\*</sup>Thermo King offers several electric standby options. See your Thermo King dealer for specific unit performance on the option that best suits your needs.

Heating Capacity	Engine Power w/ETV
BTU/hr	50,000

(System net heating capacity at 35/0°F ambient)

Airflow Capacity	
Volume at 0 Pa static pressure	3,350 ft <sup>3</sup> /min
Engine: four cylinder, direct injection, liquid cooled	
Model	TK486V25
RPM at High Speed	2,200
RPM at Low Speed	1,450
Hp Rating at 2,200 RPM	24.0
Oil Capacity	12 qt
Maintenance Interval	3,000 hrs
Compressor: lightweight aluminum alloy body, heads and sump	
Model	X430L
Displacement	30.0 in <sup>3</sup>
Refrigerant: (Zero Ozone Depletion Potential (ODP), internationally approved)	R404A
Charge	14.5 lbs
System Weight	1,863 lbs
50 gallon fuel tank (with bracket)	76 lbs

# All Thermo King equipment is backed by the Thermo King dealer service network, with locations all across North America.



