

## SPECIFICATION SHEET

# PRECEDENT® S-600



#### STANDARD FEATURES

- SMART REEFER™ SR-4 Controller
- Diesel Direct Electric (DDE) architecture with ETV
- · Common Rail fuel injection
- Microchannel condenser coils
- 2-speed evaporator
- OptiSet<sup>™</sup> Plus
- CargoWatch™
- · Easy-access door design
- 50-gallon aluminum undermount fuel tank w/visual fuel level gauge
- ServiceWatch™

#### **OPTIONS**

- · Severe duty package
- Supplemental power kit
- SmartPower electric standby
  - Standard
  - High output (HO)
- SmartPower prep package
- · Remote monitoring lights
- Arctic package
- Frost plug heater
- Alternator, 65 amp, 12Vdc
- Battery charger
- Appearance options
  - LED lighting kit
  - Chrome package
- Fresh air exchange
- Fuel tanks and sensors
- · PrimAir air management products
- TracKing® telematics
- CargoLink wireless sensors

### **EPA COMPLIANCE**

EPA Emissions Compliance: Tier IV Final

#### CARB COMPLIANCE

California Air Resources Board (CARB): ULETRU (Evergreen)

#### REFRIGERATION CAPACITY

(System net cooling capacity at 100°F ambient and high speed engine operation)

	Engine Power w/ETV	Electric Power*	
	BTU/hr Watts	BTU/hr Watts	
35°F	60,000 17,584	57,000 16,705	
0°F	32,000 9,378	34,000 9,964	
-20°F	20,000 5,861	20,000 5,861	

<sup>\*</sup>Thermo King offers several electric standby options. See your Thermo King dealer for specific unit performance on the option that best suits your needs.

Heating Capacity	Engine Power w/ETV
BTU/hr	59,500
(System net heating capacity at 35/0°F ambient)	

Airflow Capacity	
Volume at 0 Pa static pressure	3,350 ft <sup>3</sup> /min
Engine: four cylinder, direct injection, liquid cooled	
Model	TK488CR
RPM at High Speed	2,050
RPM at Low Speed	1,250
Hp Rating at 2,050 RPM	33.0
Oil Capacity	12 qt
Maintenance Interval	3,000 hrs/4,000 hrs
Compressor: lightweight aluminum alloy body, heads and sump	
Model	X430L
D. I.	200:3

Model	X430L
Displacement	30.0 in <sup>3</sup>
Refrigerant: (Zero Ozone Depletion Potential (ODP), internationally approved)	R404A
Charge	14.5 lbs
System Weight	1,872 lbs
50 gallon fuel tank (with bracket)	76 lbs

All Thermo King equipment is backed by the Thermo King dealer service network, with locations all across North America.

