



SPECIFICATIONS

DIMENSIONS INCHES



Condenser



Evaporator

EVAPORATOR AIRFLOW

230 ft³/min

REFRIGERANT

HFC R-134a

AIR CONDITIONING CAPACITY*

BTUs/hr	Watts
8,000	2,342

TRACTOR ALTERNATOR

Minimum Size Required
270A

CONTROLS

The TriPac HMI Controller features a simple three-knob design for easy operation.

HEATING CAPACITY

BTUs/hr	Watts
7,500	2,200
13,600	3,986 (optional)

SYSTEM WEIGHT (APPROX.)

Battery Box w/Cables:	480 lbs
Evap:	66 lbs
Condenser w/Drier:	26 lbs

WARRANTY SUMMARY

Terms of the Thermo King Limited Express Warranty are available upon request.

EXTENDED WARRANTY

Several Extended Warranty options are available for your TriPac system. Choose a flexible program and select the warranty period, deductible and hours of operation that best meet your needs. Ask your local Thermo King dealer about nationwide coverage plans.

***AHRI STD** - Standard for Performance Rating of unitary Air Conditioning and Heat Pumps for the rating conditions of 80F Box, 50% humidity, and 95°F ambient.



Thermo Gard® Assurance

CHOOSE FROM A COMPLETE LINE OF CUSTOMIZABLE FLEET MANAGEMENT OPTIONS FOR YOUR BUSINESS!

Thermo King SVC's Thermo Gard Assurance guaranteed maintenance program includes set programs and a wide variety of coverage options to fit the needs of your business.