



## SPECIFICATIONS

Feature	Description
Communications	Cellular (Global GSM/GPRS), Wi-Fi (802.11 b/g/n), Dual Mode
Compatibility	SB, SB-30 , Precedent (Wi-Fi available for SB-30 and Precedent only)
Serial Ports	2 RS-232
Back-up Battery	Standard
Memory	32 Mb
Power Usage	10-16 VDC
Operational Temperature Range	-40°C to +85°C
Dimensions (LxWxH)	(6.22"x3.19"x2.02")
Environmental	RoHS Compliant
Protection	0 to 36V reversed
I/Os	Digital and analog I/Os for door and fuel sensors
Agency Regulatory Certifications	FCC, ICC, CE, PTCRB
TracKing Firmware Upgrade	Over the air (OTA)
Refrigeration Unit Firmware Upgrade	OTA upgrades with TracKing Wi-Fi & TracKing dual mode
Remote OptiSet+	Upload cargo profiles over the air (OTA)

## OPTIONS

### Sensors

- Wireless CargoLink™ Door Sensors
- CargoWatch™ Air Temperature Sensors
- CargoWatch™ Food Safe Temperature Sensor
- Ultrasonic Fuel Level Sensor

### Data Loggers and Printers

- DAS
- TouchPrint
- CargoPrint

### ThermoLite™ Solar Panels

### Mi-Jack Systems Trailer Door Lock Connectivity

